

RPTNC BULKHEAD JACK TO PLUG LIGHTNING ARRESTOR



The AccelTex Solutions bi-directional gas discharge tube lightning arrestor protects outdoor equipment from the buildup and discharge of static electricity that affects the operation and lifespan of your network.

Part Number: ATS-LP-RPTNC-BHJ-P

> ELECTRICAL SPECIFICATIONS

Impedance: 50Ω
Frequency Range: DC-5.85 GHz
Discharge Voltage: 90V
VSWR: ≤1.7
Insertion Loss: ≤0.3dB

Center Conductor Contact Resistance: ≤ 10mΩ
Outer Conductor Contact Resistance: ≤ 2.5mΩ
Dielectric Withstand: 1500V RMS
Insulation Resistance: ≥ 5000MΩ

> MECHANICAL SPECIFICATIONS

Connector 1 Style: RPTNC Bulkhead Jack
Connector 2 Style: RPTNC Plug
Mating: 7/16-28UNEF-2A and 7/16-28UNEF-2B
Durability: ≥ 500 Cycles
Installation: DIN Rail Mount and L Bracket

Body: Nickel Plated Brass
Insulator: Teflon
Contact Socket: Gold Plated Bronze
Contact Pin: Gold Plated Bronze

> ENVIRONMENTAL SPECIFICATIONS

Operating Temperature: -40 to 185°F (-40 to 85°C)

> STANDARDS, TESTING AND CERTIFICATIONS

IEC 60169-17
ROHS 2011/65/EU Compliant

> WARRANTY

1 Year Limited Warranty