



LT-LPIGE-802GBTME

- Rail DIN mounting
- Copper ports: 8x10/100/1000Tx, RJ45, PoE802.3af/at
- Optical-fibre ports 2 or 4 x 100/1000 Mbit/s SFP
- Layer 3 static routing
- with management, ring-capable
- Power supply 44-56VDC, redundant

Robust and high quality industrial switches for the use in 10/100/1000 IEEE802.x Ethernet IP-networks with high data loads. All copper ports are PoE+ capable. The switches may be used in redundant ring topologies with a recovery time of less than 50ms. Two or four SFP bays allow the use of fiber optic with multimode or singlemode fiber. With the high data rate of the backplane these switches are predestinated for the use in networks with a high traffic load as for instance in video surveillance. The powerful management allows the use of these switches in big and structured networks. The switch is made for mounting on DIN-rail bars

Product information

Brief description

Industrial switch with management and PoE+

Special Feature for Video Networks

Video-friendly features:

Extra high backplane performance for a smooth video transmission with all ports assigned. Support of Jumbo Frames up to 9600Bytes by 100MBit/s.

Active monitoring of the camera

Switch-powered cameras by PoE are constantly monitored. In case of a camera failure the switch automatically restarts the camera. If this is not possible the switch alarms by SNMP.

Active monitoring PoE-supply

The switch alarms by SNMP in case of sudden excessive power consumption by a defect camera for example.

Active management of the PoE-performance

The PoE-ports can be started by time intervals so as to prevent an overload of the PoE power supplies.

Special Features

USB config port: For FW-update, backup, restore, boot up and syslog, USB2.0 A-Typ

Technical data

Copper Ports	8 x 10/100/1000TX, PoE+ 802.3af/at
Fiber Ports	LT-PIGE-802-GBTME: 2 x 100/1000, SFP (Bei Kupfer-SFPs Typen AC-SFP-xxx verwenden) LT-PIGE-804-BGTME: 4 x 100/1000, SFP (Bei Kupfer-SFPs Typen AC-SFP-xxx verwenden) We recommend the use of our barox SFPs. We do not test or guarantee the compatibility of our devices with SFPs of other manufacturers.
Console Port	RS232, 115,2kBit/s, 8, N, 1, RJ45
Supply Voltage	48-55VDC, redundant power possible, screw clamp
Power Consumption	Max. 15W (without PoE)
Operating temperature	-40°C to +75°C
Power Loss	109 BTU/h
Dimensions	142x56x99mm (Height x Width x Length)
Weight	Gross weight [kg] 1.293 Net weight [kg] 1.035
Test Standards	EMV: IEC61000-4-2, 4-3, 4-4, 4-5, 4-8, IEC61000-6-2, 6-4 Free fall: IEC60068-2-32 Shock: IEC60068-2-27 Vibration: IEC60068-2-6
Backplane	20 GBit/s
MAC Table	8k
Configuration	Console, Webserver, Telnet, CLI, SNMP v1/v2/v3, TFTP, SSH, SSL, RMON, USB
Port Settings	Per Port: Port disable/enable, Auto negotiation 10/100/1000, Full- & halfduplex, Flow Control disable/enable, data rate
Port Status Display	Per Port: Data rate, Duplex, Link, Flow Control, Auto Negotiation, Trunk
VLAN	max. 64 VLAN ID & 802.1Q VLAN & Port Based
Link Aggregation	802.3ad LACP, static Trunk, 12 groups with 16 ports
QoS	Class of Service IEEE 802.1p per port 4 priorities
Security	FCC Class A, CE, UL

Multicast

IGMP v1, v2

Standards

802.3, 10Base-T Ethernet
802.3u, 100BaseTX und 100BaseFX Fast Ethernet
802.3ab, 1000Base-T
802.3z, 1000Base-X
802.3x, Flow Control und Back Pressure
802.1d, Spanning Tree
802.1w, Rapid Spanning Tree
802.1s, Multiple Spanning Tree
ITU-TG.8032 / Y.1344 Ethernet Ring Protection Switch
802.3ad, Port Trunk mit LACP
802.3af Power over Ethernet
802.3at Power over Ethernet PoE+
802.1p, Class of Service
802.1q, VLAN Tag
802.1x, User Authentication (RADIUS)
802.1ab LLDP
